

Multi-end roving PP2



Multi-end roving for glass mat thermoplastic sheets (GMT)

Product description:

PP2 multi-end roving product is suitable for the production of glass fiber reinforced thermoplastic sheets (GMT) with its easy choppability and uniform fiber distribution.

Features and benefits:

- Manufacturing in accordance with ISO 9001:2015 conditions
- Very low static load
- Good unwinding
- Good wettability
- Very good choppability and uniform fiber distribution
- Low fuzz

Product specifications:

Glass type	E	Sizing content (%)	0.75 ± 0.10
Tex (g/1000 m)	2400 ± 5%	Split tex (g/1000 m)	Nom. 80
Fiber diameter (μ)	Nom. 14	Moisture content (%)	max. 0.1
Sizing type	Silane	Resin compatibility	Polypropylene

End-use markets:

- Glass mat thermoplastics (GMT)

Bobbin dimensions:

Inner diameter (mm): 100
External diameter (mm): 300
Height (mm): 260
Weight (kg): 23

Packing information:

Packaging	With / Without paper body
Number of layers per pallet	4
Number of bobbins per layer	12
Number of bobbins per pallet	48
Pallet dimensions (cm)	95 x 125
Pallet height (cm)	125
Average pallet net weight (kg)	1000



Please scan the QR code
for more detailed
packaging information.

Storage conditions:

Product should be stored in dry area at room temperature and relative humidity of approx 65%. Product should be conditioned for 24 hours in the work area prior to use. In case of partial usage, package should be re-sealed.

Form No: EN-3142-1 Revision Date: 02.2025